

BATTIPAV™

EXPERT 600



TECHNICAL SPECIFICATIONS

| | |
|---|--|
| Blade (Ø mm)* | 600 |
| Max. straight cutting length (mm) | 750 |
| Max. cutting depth for straight cut (mm) | 220 |
| Max. size tile for diagonal cutting (mm) | 412 x 412 |
| Max. cutting depth with 2 runs (mm) | 285 |
| Working table dimension (L x W) (mm) | 443 x 520 |
| Tool hole (Ø mm) | 25.4 |
| Rotation speed (rpm) | 1400 |
| Motor type | 1 phase - 230V ~ 50 Hz 3 phase - 400V ~ 50 Hz |
| Motor power (HP / kW, A) | 1 phase - 4.5 / 3.5, 8.0 3 phase - 5.5 / 4.0, 8.0 |
| Water recycling pump type | S3 |
| Water tank capacity (Min. / Max.) (ltrs.) | 19 / 25 |
| Thermic protection (°C) | 160 |
| Amperometrical protection (A) | 10 - 16 |
| Net weight (kg) | 81 |

OPTIONAL




Wheels kit



SRS kit



Laser instrument



45° angle cutting accessory

*Diamond blade not included.

Ideal for the building sector. Innovative design with high tech solutions, very precise, compact, light and strong, it's suitable for cutting bricks, poroton blocks, marble blocks and all the different kind of materials for the building sector.

Distributor:



شركة الوسام للتجارة ذ.م.م.
AL WISAM TRADING CO. L.L.C.

☎ : (+971 6) 539 03 83 ✉ : awtc@alwisamllc.com
☎ : (+971 6) 539 03 84 🌐 : www.alwisamllc.com
📍 : 81933, Sharjah - U.A.E.