



BATTIPAV™

EXPERT 700



TECHNICAL SPECIFICATIONS		OPTIONAL
Blade (Ø mm)*	700 / 650	 SRS kit
Max. straight cutting length (mm)	Blade Ø700 = 550 Blade Ø650 = 580	
Max. cutting depth for straight cut (mm)	Blade Ø700 = 270 Blade Ø650 = 240	
Max. size tile for diagonal cutting (mm)	Blade Ø700 = 389 x 389 Blade Ø650 = 410 x 410	
Max. cutting depth with 2 runs (mm)	340	
Working table dimension (L x W) (mm)	515 x 520	
Tool hole (Ø mm)	Blade Ø700 = 25.4 Blade Ø650 = 25.4	
Rotation speed (rpm)	1400	
Motor type	1 phase - 230V ~ 50Hz 3 phase - 400V ~ 50Hz	
Motor power (HP / kW, A)	1 phase - 4.5 / 3.5, 8.0 3 phase - 5.5 / 4.0, 8.0	
Water recycling pump type	S3	 45° angle cutting accessory
Water tank capacity (Min. / Max.) (ltrs.)	21 / 32	
Thermic protection (°C)	160	
Amperometrical protection (A)	10 - 16	
Net weight (kg)	100.5	
Wheels kit	Included	

*Diamond blade not included.

Ideal for the building sector. Innovative design with high tech solutions, very precise, compact, light and strong, it's suitable for cutting bricks, poroton blocks, marble blocks and all the different kind of materials for the building sector.

• Distributor: •



شركة الوسام للتجارة ذ.م.م.
AL WISAM TRADING CO. L.L.C.

☎ : (+971 6) 539 03 83 ✉ : awtc@alwisamllc.com
☎ : (+971 6) 539 03 84 🌐 : www.alwisamllc.com
📍 : 81933, Sharjah - U.A.E.