









BATTIPAV™

PRIME 650



TECHNICAL SPECIFICATIONS		OPTIONAL
Blade (Ø mm)*	650	 SRS kit
Max. straight cutting length (mm)	640	
Extra cut (mm)**	Up to 1000 (for 650S) Up to 820	 Laser instrument
Max. cutting depth for straight cut (mm)	250	
Max. size tile for diagonal cutting (mm)	450 x 450	
Max. cutting depth for 45° angle cut (mm)	163	 B-Lock for thickness up to 40 mm
Tool hole (Ø mm)	25.4	
Rotation speed (rpm)	1400	 Side bench with rollers
Motor type	3 phase - 400V ~ 50 Hz	
Motor power (HP / kW, A)	5.5 / 4.0, 8.0	
Water recycling pump type	S3	 Extension side bench
Water tank capacity (Min. / Max.) (ltrs.)	23 / 36	
Thermic protection (°C)	160	 Side tile support
Amperometrical protection (A)	10 - 16	
Net weight (kg)	114	
Wheels kit	Included	 Long slot for side tile support
Cutting progress system	Included	

*Diamond blade not included.

** (S) code for machine includes laser instrument

Ideal for the building sector. New design with vanguard technical innovation, strong and precise, suitable for cutting brick blocks, natural stones, poroton & concrete blocks.

• Distributor: •



شركة الوسام للتجارة ط.م.م.
AL WISAM TRADING CO. L.L.C.

☎ : (+971 6) 539 03 83

✉ : awtc@alwisamllc.com

☎ : (+971 6) 539 03 84

🌐 : www.alwisamllc.com

📍 : 81933, Sharjah - U.A.E.