








BATTIPAV™

PRIME 150



TECHNICAL SPECIFICATIONS

OPTIONAL

TECHNICAL SPECIFICATIONS		OPTIONAL	
MODEL	Prime 150		Wheels kit
Blade (Ø mm)*	350		Laser instrument
Max. straight cutting length (mm)	1500		B-Block for thickness up to 40 mm
Max. cutting depth for straight cut (mm)	110		Side bench with rollers
Max. size tile for diagonal cutting (mm)	1060 x 1060		Extension side bench
Max. cutting depth with 2 runs (mm)	180		Side tile support
Max. cutting depth for 45° angle cut (mm)	80		Long slot for side tile support
Tool hole (Ø mm)	25.4		
Rotation speed (rpm)	2800		
Motor type	1 phase - 230V ~ 50 Hz 3 phase - 400V ~ 50 Hz		
Motor power (HP / kW, A)	1 phase - 3.0 / 2.2, 9.0 3 phase - 4.5 / 3.4, 9.0		
Water recycling pump type	S3		
Water tank capacity (Min. / Max.) (ltrs.)	31 / 49		
Thermic protection (°C)	160		
Amperometrical protection (A)	13		
Net weight (kg)	122.5		
Cutting progress system	Included		

*Diamond blade not included.

Ideal for the building sector. New design with vanguard technical innovation, strong and precise, it is suitable for cutting bricks, natural stones, concrete blocks, granite & marble slabs.

Distributor:



شركة الوسام للتجارة ط.م.م.
AL WISAM TRADING CO. L.L.C.

☎ : (+971 6) 539 03 83 ✉ : awtc@alwisamllc.com
☎ : (+971 6) 539 03 84 🌐 : www.alwisamllc.com

📍 : 81933, Sharjah - U.A.E.