

TS 400 F



TECHNICAL SPECIFICATIONS

MODEL	TS 400 F		
Max. blade diameter (mm)	400		
Max. depth of cut (mm)	125		
Max. depth of with 2 runs cut (mm)	230		
Max. length of cut (mm)	700		
Arbor size (Ø mm)	25.4		
Rotation speed (rpm)	2,800		
Weight (kg)	96		
Dimensions (L x W x H) (mm)	1120 x 600 x 600		
ELECTRIC MOTOR	SINGLE PHASE	SINGLE PHASE	THREE PHASE
Power (kW)	1.5	2.2	2.7
Voltage (V)	115	230	400
Frequency (Hz)	50	50	50

TS 400 F is an efficient universal masonry saw with high cutting capacity for all kinds of bricks and building blocks. You can easily plunge or bevel cut at 45 degrees for maximum versatility. The robust single-piece frame with integrated conveyor rails gives great rigidity and provides longer product life.

• Distributor: •



شركة الوسام للتجارة ذ.م.م.
AL WISAM TRADING CO. L.L.C.

☎ : (+971 6) 539 03 83 ✉ : awtc@alwisamllc.com
☎ : (+971 6) 539 03 84 🌐 : www.alwisamllc.com
📍 : 81933, Sharjah - U.A.E.