



WATER-COOLED



3 PHASE / 1 PHASE



50HZ 380-415V



DIESEL FUEL

FUJIAN DEPCO POWER GENERATION CO., LTD



## STANDARD SPECIFICATIONS

1. ENGINE  
FOUR STROKE HEAVY DUTY HIGH PERFORMANCE INDUSTRIAL DIESEL ENGINE.

2. ENGINE FILTRATION SYSTEM

- AIR FILTER
- FUEL FILTER
- FULL FLOW LUBO OIL FILTER

ALL FILTERS HAS REPLACEABLE ELEMENTS

3. COOLING SYSTEM

EFFICIENT WATER-COOLED SYSTEM WITH COMPLETE SAFETY GUARDS, DESIGNED TO COOL THE ENGINE AT HIGH AMBIENT TEMPERATURES (CONSULT US FOR DE-RATION FACTORS)

4. EXHAUST SYSTEM

HEAVY DUTY INDUSTRIAL EXHAUST SILENCER

5. CIRCUIT BREAKER TYPE

DELIXI MCCB 3POLE

GENERATING SET MODEL		DPK-DK-18
OUTPUT RATING	PRIME	STANDBY
50Hz 380-415V,3PH,1500RPM	16.0KVA	17.5KVA
	12.8KW	14.0KW

ENGINE TECHNICAL DATA		
ENGINE MAKE	DEPCO	
ENGINE MODEL	DEPCO-4L22	
GOVERNING TYPE	MECHANICAL	
NUMBER OF CYLINDERS	4	
CYLINDER ARRANGEMENT	In-line	
BORE AND STROKE (mm)	85 x 95	
DISPLACEMENT	2.156	L
ASPIRATION	Natural	
CYCLE	4 STROKE	
COMPRESSION RATIO	/	
COOLING SYSTEM	WATER-COOLING	
FREQUENCY & ENGINE SPEED	50HZ & 1500RPM	
	PRIME	STANDBY
GROSS ENGINE POWER kW	17kW	/
FUEL CONSUMPTION @ 100% L/hr	3.58	-
FUEL CONSUMPTION @ 50% L/hr	-	-

ALTERNATOR DATA	
MAKE	DEPCO
MODEL	DEPCO-13-3
NO.OF BEARINGS	1
INSULATION CLASS	H
WIRES	
INGRESS PROTECTION	IP23
EXCITATION SYSTEM	SHUNT
VOLTAGE	±1%

DIMENSION & WEIGHT	
LENGTH mm	1400
WIDTH mm	740
HEIGHT mm	850
WEIGHT*kg	540
FUEL TANK CAPACITY	30L

CONTROL PANEL	
MAKE	DATAKOM
MODEL	D100

PLEASE REFER TO DATAKOM BROCHURE FOR MORE DETAILS

## RATINGS DEFINITION

### PRIME POWER

THESE RATING ARE APPLICABLE FOR SUPPLYING CONTINUOUS ELECTRICAL POWER (AT VARIABLE LOAD) IN LIEU OF COMMERCIALY PURCHASED POWER. 10% OVERLOAD POWER IS AVAILABLE FOR 1HOUR IN 12HOURS CONTINUOUS OPERATION.

### STANDBY POWER

THESE RATING ARE APPLICABLE FOR SUPPLYING CONTINUOUS ELECTRICAL POWER (AT VARIABLE LOAD) IN THE EVENT OF A UTILITY POWER FAILURE. NO OVERLOAD IS PERMITTED.

### STANDARD REFERENCE CONDITIONS

OUTPUT RATING ARE PRESENTED AT 27°C AIR INLET TEMPERATURE, BAROMETRIC PRESSURE 100kPa, RELATIVE HUMIDITY 30%. THIS GENERATING SET IS DESIGNED TO OPERATE AT HIGH AMBIENT TEMPERATURE (UP TO 52°C), HUMIDITY (UP TO 90%) AND HIGH ALTITUDES. DE-RATION MAY APPLY, PLEASE CONSULT US FOR SPECIFIC SITE RATINGS.

### AVAILABLE OPTIONS & ACCESSORIES

WE OFFER A RANGE OF OPTIONAL FEATURES AND ACCESSORIES TO TAILOR OUR GENERATING SETS TO MEET YOUR POWER NEEDS.

#### OPTIONS

- A VARIETY OF GENERATING SET CONTROL AND SYNCHRONIZING PANELS
- ADDITIONAL PROTECTION ALARMS AND SHUTDOWNS
- WATER - FUEL SEPERATOR
- WATERJACKET HEATER
- BATTERY CHARGER

#### ACCESSORIES

- GENUINE SPARE PARTS
- AUXILIARY FUEL TANKS
- MANUAL & AUTOMATIC TRANSFER SWITCHS



شركة الوسام للتجارة ذ.م.م.

AL WISAM TRADING CO. L.L.C.

☎ : (+971 6) 539 03 83

✉ : awtc@alwisamllc.com

☎ : (+971 6) 539 03 84

🌐 : www.alwisamllc.com

📍 : 81933, Sharjah - U.A.E.

## STANDARD SPECIFICATIONS

### 6. FUEL SYSTEM

ON GENERATING SETS UP TO 750KVA, THE CHASSIS DESIGN IS INCORPORATED WITH INTEGRAL FUEL TANK WITH A CAPACITY OF APPROX 12HOURS TO 13HOURS RUNNING AT FULL LOAD. THE TANK IS SUPPLIED COMPLETE WITH FILL CAP, BREATHER, FUEL FEED AND RETURN LINES TO THE ENGINE AND DRAIN PLUG.

### 7. ALTERNATOR

#### 7.1 INSULATION SYSTEM

- THE INSULATION SYSTEM IS CLASS H
- ALL WINDINGS ARE IMPREGNATED IN EITHER A TRIPLE DIP THERMOSETTING LIQUID, OIL AND ACID RESISTING POLYESTER VARNISH OR VACUUM PRESSURE IMPREGNATED WITH A SPECIAL POLYESTER RESIN.

- HEAVY COAT OF ANTITRACKING VARNISH ADDITIONAL PROTECTION AGAINST MOISTURE OR CONDENSATION

#### 7.2 AUTOMATIC VOLTAGE REGULATOR (AVR)

- THE FULLY SEALED AUTOMATIC VOLTAGE REGULATOR MAINTAINS THE VOLTAGE REGULATION AT  $\pm 1\%$ .

#### 7.3 MOTOR STARING (OPTIONAL)

- AN OVERLOAD CAPACITY EQUIVALENT TO 300% OF THE FULL LOAD IMPEDANCE AT ZERO POWER FACTOR CAN BE SUSTAINED FOR 10 SECONDS, WHEN AREP (AUXILIARY WINDING)OPTION IS FITTED.

### 8. MOUNTING ARRANGMENT

#### 8.1 CHASSIS

THE COMPLETE GENERATING SET IS MOUNTED AS A WHOLE ON A HEAVY DUTY FABRICATED STEEL CHASSIS.

### 8.2 ANTI-VIBRATION MOUNTING DUMPER

DUMPER ARE AFFIXED BETWEEN THE ENGINE & ALTERNATOR FEET AND THE CHASSIS, THUS ENSURING COMPLETE VIBRATION ISOLATION OF ROTATING ASSEMBLY.

### 8.3 COUPLING

THE ENGINE AND ALTERNATOR ARE DIRECTLY COUPLED BY MEANS OF AN SAE FLANGE. THE ENGINE FLYWHEEL IS FLEXIBLY COUPLED TO THE ALTERNATOR ROTOR.

### 8.4 SAFETY GUARDS

THE FAN & FAN DRIVE ALONG WITH THE BATTERY CHARGING ALTERNATOR ARE SAFETY GUARD PROTECTED FOR PERSONAL PROTECTION.

### 9. TESTS

- THE GENERATING SET IS LOAD TEST BEFORE DISPATCH.
- ALL PROTECTIVE DEVICES CONTROL FUNCTIONS AND SITE LOAD CONDITIONS ARE SIMULATED. THE GENERATOR AND IT'S SYSTEMS ARE CHECKED BEFORE DISPATCH.

### 10. EQUIPMENT FINISHING

ALL MILD STEEL COMPONENTS ARE FULLY DEGREASED AND PAINTED WITH POWDER COATED PAINT TO ENSURE MAXIMUM SCUFF RESISTANCE AND DURABILITY.

### 11. EQUIPMENT FINISHING

OPERATION & MAINTENANCE MANUAL, CIRCUIT WIRING DIAGRAMS.

### 12. QUALITY STANDARDS

THE EUQIPMENT MEETS THE FOLLOWING STANDARDS:BS4999, BS5000, BS5514, IEC60034, VDE0530 AND ISO8528

### 13. WARRANTY

ALL OF THE GENERATING SETS ARE COVERED UNDER A WARRANTY POLICY FOR A PERIOD OF 1000 WORKING HOURS OR 1 YEAR (WHICHEVER COMES EARLIER) OF THE EQUIPMENT IS IN LINE WITH MANUFACTURERS WARRANTY TERMS AND CONDITIONS.

IN LINE WITH CONTINUOUS PRODUCT DEVELOPMENT, WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT NOTICE.